



# Rogue Outcast 1 Beam

Rogue Outcast 1 Beam is an IP65 moving head that outputs an intensely bright 300 W beam with 14 position color wheel individually controllable for solid and split hues. The outdoor-ready unit raises the bar in dynamic effect options with its ability to focus down to a pencil-thin 1° beam for tight aerals, overlapping 8 and 5-facet prisms, frost for even light distribution, and 17 static gobos for even more creative options. Control is over DMX and RDM.

Coming Soon



## At a Glance

- Fully featured, IP 65 rated, high-powered beam fixture with an USHIO 300 W 6500 K, 8,000 hour lamp, a single color wheel, single static gobo wheel, and overlapping prisms
- Rugged housing designed to withstand the elements in a temporary outdoor setting
- Fast and precise movement of pan and tilt functions
- Individually controllable and layerable 8 and 5-facet prisms
- 14 position color wheel for solid and split colors
- Frost for even light distribution
- Tight 1° beam for extremely focused areal effects
- 17 static gobos for massive visual impact
- DMX and RDM protocol control
- True 1 compatible power input

# Specifications

## Optical

- Light Source: USHIO NSL-300W lamp, 6782 K, 8,000 hours life expectancy
- Color Temperature (at full): 6782 K
- CRI: 81.5
- Beam Angle: 1°
- Field Angle: 2°
- Illuminance (total): 149,700 lux @ 15 m

## Dynamic Effects

- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors: 14 + white, split colors, continuous scroll at variable speeds
- Gobos: 17 + open (17 metal), continuous scroll at variable speeds
- Dimmer: Motorized
- Shutter/Strobe: Motorized
- Focus: Motorized
- Frost: Motorized
- Prism: 5 Facets, motorized, rotating
- Prism: 8 Facets, motorized, rotating
- Move-in-Black: Yes

## Construction / Physical

- Dimensions: 16.23 x 12.2 x 23.19 in (412.2 x 310 x 589.1 mm)
- Weight: 67.0 lb (30.4 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

## Connections

- Power Connection: Edison plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

## Control

- Control Protocol: DMX, RDM
- DMX Channels: 16 or 19
- Modes/Personalities: 2 personalities (16, 19)

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 451 W, 3.81 A @ 120 V, 60 Hz
- Power and Current: 436 W, 2.09 A @ 208 V, 60 Hz
- Power and Current: 408 W, 1.76 A @ 230 V, 50 Hz

## Certifications / Qualifications

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use
- Temperature (Ambient): 14 °F to 104 °F (-10 °C to 40 °C)

## What's Included

- Rogue Outcast 1 Beam
- Seetronic Powerkon IP65 power cord
- 2 Omega brackets with mounting hardware
- Quick Reference Guide

## Optional Accessories

- Professional Clamps : CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- DMX Cables
- IP Rated Seetronic® Powerkon Extensions

