GigBAR Move + ILS

- 5-in-1 lighting system that includes moving heads, derbies, washes, a laser and strobe effect pre-mounted on a single bar
- Integrated Lighting System (ILS) is a complete lighting ecosystem technology that provides an advanced, coordinated light show across multiple fixture types
- Separate color and gobo wheels allow for creative programming
- · Totem Mode keeps the moving heads focused on the dance floor
- System includes a tripod, wireless footswitch, RF remote and FREE carry bags to ensure quick setup
- Built-in UV LEDs illuminate florescent objects for dazzling blacklight effects
- Easy control via stand-alone, DMX, wireless RF remote or wireless footswitch

Specifications

- DMX Channels: 3, 28, or 50
- Colors (moving head): 9 + open, split colors, continuous scroll
- Gobos (moving head): 9 + open, continuous scroll
- Light Source (pars): 3 LEDs (hex color RGBAW+UV) 6 W (2 A)
- Light Source (strobe): 4 LEDs (cool white) 5 W (1.2 A)
- Light Source (derby): 8 LEDs (2 red, 2 green, 2 blue, 2 white)
 6.5 W (2 A)
- Light Source: (moving head) 1 LED (cool white) 32 W, (3 A)
- Light Source: (Laser) 638 nm/30mW (red) laser diode, 520 nm/20 mW (green) laser diode, 450 nm/100 mW (blue) laser diode
- Strobe Rate: 0 to 30 Hz
- Stand Height: 4.8 ft to 8.3 ft (1.5 to 2.5 m)
- Beam Angle (moving head): 17°
- Beam Angle (pars): 22°
- Beam Angle (strobe): 30°
- Coverage Angle (derby): 131°
- Coverage Angle (laser): 93°
- Illuminance (pars): 1,205 lux @ 2 m (per par)
- Illuminance (moving head): 5,140 lux @ 2 m (per head)
- Illuminance (strobe): 130 lux @ 2 m
- Footswitch Max Unobstructed Distance: 100 ft (30.5 m)
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 250 W, 3 A @ 120 V, 60 Hz
- · Optional Controllers: RF
- Classified per 21 CFR 1040.10 & .11
- Complies with US FDA CDRH laser safety standards 21 CFR 1040.10 & 1040.11
- Approvals: CE, UKCA, RoHS, FCC, FDA



- Weight (bar only): 31 lbs (14 kg)
- Size: 43 x 5.7 x 17.7 in (1100 x 144 x 449 mm)



