



ZERO-S



Monochromatic: Management through:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Stainless steel face AISI 316L and pure aluminium body powder coated painted.
- Inground / ceiling recessed / wall recessed installation.
- Tempered glass.
- Dimmable

Code	No.LED	Colour*	Watt	Lumen	Colour Temperature	Dimensions	Diameter	Max. Kg	Voltage	Beam**	IP	Dimmable
LGR.088	1	COOL WHITE	3W	130lm	5600K	54x40mm	40mm	1000Kg	12VDC	10°	IP67	Dimmable
LGR.089	1	WARM WHITE	3W	110lm	3000K	54x40mm	40mm	1000Kg	12VDC	10°	IP67	Dimmable
LGR.132	1	WARM WHITE	3W	110lm	2700K	54x40mm	40mm	1000Kg	12VDC	20°	IP67	Dimmable
LGR.104	1	BLUE	3W	-	-	54x40mm	40mm	1000Kg	12VDC	10°	IP67	Dimmable
LGR.107	1	GREEN	3W	-	-	54x40mm	40mm	1000Kg	12VDC	10°	IP67	Dimmable

*Other colours available upon request.
 **Available in 20° & 30° degrees upon request.

