




AU-U22-DA

DANTE 2x2 CHANNEL USB 2.0 ADAPTER

AU-U22-DA from TiGHT AV allows for transmitting two channels of USB audio to your Dante network and simultaneously receiving two channels of Dante Audio. It supports sample rates up to 48kHz, using Audinate's original Dante Ultimo chip.

Featuring class-compliant drivers, the AU-U22-DA allows for connecting any computer or mobile device that supports USB audio, to a Dante network without any software installation needed. Simply plug it in and get to work!

The package includes two types of USB cables: Type-C to Type-C and Type-C to Type-A. Power is supplied via PoE or by USB power from connected source device.



SPECIFICATIONS

DANTE

Sample Rate:	48kHz
Bit Depth:	24
Dante Device Latency:	1, 2 or 5 ms (configurable using Dante Controller)
Network Transport:	Dante Audio over IP AES67 RTP
Model Name:	AU-U22-DA

GENERAL

USB:	USB 2.0 device, Type-C connector
Operation Temperature:	-5 to +55°
Storage Temperature:	-25 to +70°
Power:	802.3af PoE or USB power
Power Consumption:	9W (Max)
USB Power Delivery:	5V, 1.5A (When POE is applied)
Dimension (WxHxD):	115 x 34 x 28 mm
Net Weight:	70 g
Cable length:	20 cm
Compliance:	FCC, CE
Environmental:	RoHs, WEEE

PACKAGE LIST

1 x AU-U22-DA	1 x Type-C to Type-A USB cable (20cm)
1 x Type-C to Type-C USB cable (20cm)	1 x User Manual

KEY FEATURES

- Plug and play
- Supports 2x2 channels of bi-directional USB audio
- USB 2.0, USB Type-C connector
- Supports USB volume control from connected devices
- USB power delivery up to 5V 1.5A to connected tablets or mobile phones
- Dante and AES67 support
- 24-bit audio support
- Supports 802.3af PoE
- Dante Controller and Dante Domain Manager compatible

TIGHT POLICY

Faulty product - minimal down time.

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

Your investment - built to last.

All TiGHT AV products come with a five year limited warranty.

